

## PRODUCT DATA SHEET

C6729

**3-Port Uni-Directional Coupler:** Consists of a main line and a coupled line. One end of the coupled line is internally terminated, while the other end serves as a coupled port. Ideal for sampling and monitoring power in one direction at a given time. It is necessary to physically reverse the orientation of the unit to change from a forward to a reverse power measurement.

### Features:

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

### Electrical Specifications:

Frequency: 0.01 - 1000 MHz  
 Power: 50 W CW  
 Coupling:  $30 \pm 1.0$  dB Max.  
 Insertion Loss: 0.7 dB Max.  
 Flatness:  $\pm 0.5$  dB Max.  
 VSWR (ML): 1.30:1 Max.  
 Directivity: 20 dB Min.

### Mechanical Specifications:

Type: Connectorized  
 Material: Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F  
 Type I Class 3 (Yellow Iridite)  
 RoHS Compliant Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature: -60°C to +85°C  
 Humidity: 95% Non-Condensing  
 Size: 5.2 x 2.27 x 1.69"

### Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)
C6729-10	N Female	N Female	N Female
C6729-12	N Female	N Female	SMA
C6729-13	N Female	N Female	BNC
C6729-102	SMA	SMA	SMA

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



# WERLATONE

Model C6729




## PRODUCT DATA SHEET


C6729

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**



This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 3933	1/06	CS
B	ECN 9696	11/30/2018	RB

**NOTES: UNLESS OTHERWISE SPECIFIED**

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
- CONNECTORS:**  
J1, J2: N FEMALE  
J3: BNC FEMALE



		UNLESS OTHERWISE SPECIFIED		OWN	DATE	 WERLATONE  SINCE 1965		17 Jon Barrett Rd Patterson, NY 12563	
		INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		SD	2/11/2019	 WERLATONE  SINCE 1965			
		DIMENSIONS PER ASME Y14.5M-2009		CHK	DATE				
		PARENTHESES FOR REF ONLY		CS	2/11/2019	TITLE		OUTLINE	
		DIMENSIONS ARE IN INCHES		ENGR	DATE				
		DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		CS	2/27/2002	SIZE CAGE CODE DWG NO		REV	
		TOLERANCES:		INFR	DATE				
		ANGLES ± 2°		QA	DATE	SCALE: 1:1.5		SHEET 1 OF 1	
		3 PL ± .005 [13]		RLSE	DATE				
		2 PL ± .015 [38]		THIRD ANGLE PROJECTION					
		REMOVE ALL BURRS AND SHARP EDGES R.01 MAX		APPLICATION					
		CONCENTRICITY MACHINED DIA. .002 FIM		NEXT ASSY USED ON					
		MACHINE TOOL MISMATCH .003 MAX							

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com