

PRODUCT DATA SHEET

D9392

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

Electrical Specifications:

Frequency: 500 - 2500 MHz
Power: 500 W CW
Insertion Loss: 0.3 dB Max.
VSWR: 1.35:1 Max.
Phase Balance: $\pm 5^\circ$ Max.
Amplitude Balance: 0.3 dB Max.
Isolation: 15 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Weight: 13 oz.
Size: 4.7 x 2.0 x 1.1"

Connector Configurations:

| Model | Sum Port (J1) | Input/Output (J2) | Input/Output (J3) |
|----------|---------------|-------------------|-------------------|
| D9392-10 | N Female | N Female | N Female |
| D9392-12 | N Female | SMA | SMA |


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.



WERLATONE

Model D9392

Combiners In-Phase Connectorized




PRODUCT DATA SHEET


D9392

Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:



Isolation:



Phase Balance:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.

| REVISION HISTORY | | | |
|------------------|-----------------|----------|----------|
| REV. | REVISION RECORD | DATE | APPROVED |
| - | INITIAL RELEASE | 6/20/12 | CS |
| A | ECN 9696 | 4/1/2020 | RB |

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (CLEAR IRIDITE)**
- CONNECTORS:
J1-J3: N FEMALE**



| | | | | |
|--|--|------|----------|--|
| UNLESS OTHERWISE SPECIFIED | | SD | DATE | 17 Jon Barrett Rd Patterson, NY 12563 |
| INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100 | | CHK | DATE | |
| DIMENSIONS PER ASME Y14.5M-2009 | | CS | 4/1/2020 | |
| PARENTHEetical INFO FOR REF ONLY | | ENGR | DATE | |
| DIMENSIONS ARE IN INCHES | | INPR | DATE | |
| DIMENSIONAL LIMITS APPLY BEFORE FINISHES | | QA | DATE | |
| TOLERANCES: | | RLSE | DATE | |
| ANGLES ± 2° | | | | |
| 3 PL ± .005 [13] | | | | |
| 2 PL ± .015 [38] | | | | |
| REMOVE ALL BURRS AND SHARP EDGES R.01 MAX | | | | |
| CONCENTRICITY MACHINED DIA. .002 FIM | | | | |
| MACHINE TOOL MISMATCH .003 FIM | | | | |
| THIRD ANGLE PROJECTION | | | | |
| APPLICATION | | | | |
| NEXT ASSY | | | | |
| USED ON | | | | |
| TITLE | | | | |
| SIZE | | | | |
| CAGE CODE | | | | |
| DWG NO | | | | |
| REV | | | | |
| SCALE | | | | |
| SHEET 1 OF 1 | | | | |

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com