



PRODUCT DATA SHEET

D10149

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

Electrical Specifications:

Frequency: 2000 - 6000 MHz
Power: 200 W CW
Insertion Loss: 0.6 dB Max.
VSWR: 1.45:1 Max.
Phase Balance: $\pm 5^\circ$ Max.
Amplitude Balance: 0.25 dB Max.
Isolation: 15 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Weight: 0.6 lbs.
Size: 2.9 x 2.7 x 1.06"

Connector Configurations:

Model	Sum Port (J1)	Input/Output (J2)	Input/Output (J3)
D10149-10	N Female	N Female	N Female
D10149-12	N Female	SMA	SMA
D10149-13	N Female	BNC	BNC
D10149-102	SMA	SMA	SMA

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.



WERLATONE

Model D10149

Combiners In-Phase Connectorized




PRODUCT DATA SHEET


D10149

Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:



Isolation:




Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV	REVISION RECORD	DATE	APPROVED
-	Initial Rls	9/10/2014	BW

		UNLESS OTHERWISE SPECIFIED		DWN	DATE	<div><div>W</div><div>WERLATONE SINCE 1965</div></div>		17 Jon Barrett Rd Patterson, NY 12563	
		• INTERPRET DRAWING LAW MIL-STD-100		NH	09/10/14				
		• DIMENSIONING PER ASME Y14.5M-2009		CHK	DATE				
		• PARENTHEetical INFO FOR REF ONLY		BW	09/10/14				
		• DIMENSIONS ARE IN INCHES		ENGR	DATE	TITLE			
		• DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		NH	09/10/14	Outline			
21242-300		• TOLERANCES: ANGLES ± 2- 3 PL ± .005 2 PL ± .015		MFGR	DATE				
NEXT ASSY				QA	DATE	SIZE	CAGE CODE	DWG NO	REV
USED ON						A	28812	21242-500	-
APPLICATION		THIRD ANGLE PROJECTION 		RLSE	DATE	SCALE	1:2		SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com