



PRODUCT DATA SHEET D9462

Werlatone® *Mismatch Tolerant*® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone**® designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Isolation Custom Designs Available

Electrical Specifications:

Frequency: 1000 - 2500 MHz

Power: 100 W CW
Insertion Loss: 0.6 dB Max.
VSWR: 1.40:1 Max.
Phase Balance: ± 4° Max.
Amplitude Balance: 0.35 dB Max.
Isolation: 8 dB Min.

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to +75°C Storage Temperature: -60°C to +85°C Weight: 9 oz. (-102)

Size: 4.75 x 2.3 x 0.75"

Connector Configurations:

Model Sum Port (J1) Input/Output (J2-J9)

D9462-102 SMA SMA

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com







PRODUCT DATA SHEET D9462

Performance Data (Specifications subject to change without notice):

VSWR:

Insertion Loss:





1600

Frequency (MHz)

1900

2200

2500


For In-Building Applications:




Phase Balance:

1000

1300



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com