



## PRODUCT DATA SHEET

C10665

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

### Features:

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

### Electrical Specifications:

Frequency: 1.5 - 32 MHz  
Power: 3000 W CW  
Coupling:  $40 \pm 1.0$  dB Max.  
Insertion Loss: 0.15 dB Max.  
Flatness:  $\pm 0.5$  dB Max.  
VSWR (ML): 1.10:1 Max.  
Directivity: 25 dB Min.

### Mechanical Specifications:

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F  
Type I Class 3 (Yellow Iridite)  
RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Humidity: 95% Non-Condensing  
Size: 4.0 x 2.0 x 1.5"

### Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10665-10	N Female	N Female	N Female	N Female
C10665-12	N Female	N Female	SMA	SMA
C10665-13	N Female	N Female	BNC	BNC

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




## PRODUCT DATA SHEET


C10665

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**


This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	3/25/19	RB

**NOTES: UNLESS OTHERWISE SPECIFIED**

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
- CONNECTORS:**  
**J1,J2: N FEMALE**  
**J3,J4: SMA FEMALE**



<div>UNLESS OTHERWISE SPECIFIED</div> <div>INTERPRET DRAWING IN MIL-STD-100</div> <div>DIMENSIONS PER ASME Y14.5M-2009</div> <div>PARENTHESES FOR REF ONLY</div> <div>DIMENSIONS ARE IN INCHES</div> <div>DIMENSIONAL LIMITS APPLY BEFORE PROCESSES</div> <div>TOLERANCES:</div> <div>    ANGLES ± 2°</div> <div>    3 PL ± .005 [13]</div> <div>    2 PL ± .015 [38]</div> <div>REMOVE ALL BURRS AND SHARP EDGES R.01 MAX</div> <div>CONCENTRICITY MACHINED DIA. .002 FIM</div> <div>MACHINE TOOL MISMATCH .003 MAX</div>		DWN	DATE	<div><div> WERLATONE</div><div>SINCE 1965</div></div> <div>17 Jon Barrett Rd</div> <div>Patterson, NY 12563</div>
		SD	3/25/2019	
		CHK	DATE	
		CS	3/25/2019	
<div>NEXT ASSY</div> <div>USED ON</div>	ENGR	DATE	<div>TITLE</div> <div>OUTLINE</div> <div>SIZE CAGE CODE DWG NO</div> <div>B 21399-500</div>	<div>REV</div> <div>A</div>
	INFR	DATE		
	QA	DATE		
	RLSE	DATE		
<div>APPLICATION</div>		<div>SCALE</div> <div>1:1</div>		<div>SHEET 1 OF 1</div>
<div>THIRD ANGLE PROJECTION</div>				

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com