

## PRODUCT DATA SHEET

C6265

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

### Features:

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

### Electrical Specifications:

Frequency: 500 - 3000 MHz  
Power: 500 W CW  
Coupling:  $50 \pm 1.0$  dB Max.  
Flatness:  $\pm 0.75$  dB Max.  
Insertion Loss: 0.2 dB Max.  
VSWR (ML): 1.30:1 Max.  
Directivity: 20 dB Min.

### Mechanical Specifications:

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F  
Type I Class 3 (Yellow Iridite)  
RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Humidity: 95% Non-Condensing  
Size: 3.0 x 3.0 x 1.09"

### Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C6265-10	N Female	N Female	N Female	N Female
C6265-12	N Female	N Female	SMA	SMA
C6265-20*	7/16 Female	7/16 Female	N Female	N Female
C6265-22*	7/16 Female	7/16 Female	SMA	SMA
C6265-23*	7/16 Female	7/16 Female	BNC	BNC
C6265-41	SC Female	SC Female	N Female	N Female
C6265-43	SC Female	SC Female	SMA	SMA
C6265-627*	7/16 Female	7/16 Male	N Female	N Female
C6265-714	N Male	N Female	N Female	N Female
C6265-727*	7/16 Male	7/16 Female	N Female	N Female
C6265-728*	7/16 Male	7/16 Female	SMA	SMA

(7/16 Mainline Connector option increases case height to 1.59")

**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com



# WERLATONE

Model C6265

Connectorized Directional Couplers




## PRODUCT DATA SHEET


C6265

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

A

3