
WERLATONE

Model C9043
Connectorized Directional Couplers



PRODUCT DATA SHEET **C9043**

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency:	500 - 3500 MHz
Power:	500 W CW
Coupling:	50 ± 1.0 dB Max.
Insertion Loss:	0.25 dB Max.
Flatness:	± 1.00 dB Max.
VSWR (ML):	1.35:1 Max.
Directivity:	15 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Humidity:	95% Non-Condensing
Size:	3.0 x 3.0 x 1.09"


Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C9043-10	N Female	N Female	N Female	N Female
C9043-12	N Female	N Female	SMA	SMA
C9043-20*	7/16 Female	7/16 Female	N Female	N Female
C9043-22*	7/16 Female	7/16 Female	SMA	SMA
C9043-23*	7/16 Female	7/16 Female	BNC	BNC
C9043-41	SC Female	SC Female	N Female	N Female
C9043-43	SC Female	SC Female	SMA	SMA
C9043-627*	7/16 Female	7/16 Male	N Female	N Female
C9043-727*	7/16 Male	7/16 Female	N Female	N Female
C9043-728*	7/16 Male	7/16 Female	SMA	SMA

(7/16 Mainline connector option increases case height to 1.59")


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved




Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/27/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED
1. **MATERIAL: ALUMINUM 6061-T6**
2. **FINISH: CHEM FILM PER MIL-DTL_5541F TYPE I CLASS 3 (YELLOW IRIDITE)**

		UNLESS OTHERWISE SPECIFIED	DWN	DATE
		• INTERPRET DRAWING IAW MIL-STD-100 • DIMENSIONING PER ASME Y14.5M-2009 • PARENTHETICAL INFO FOR REF ONLY • DIMENSIONS ARE IN INCHES • DIMENSIONAL LIMITS APPLY BEFORE PROCESSES • TOLERANCES: ANGLES ± 2° 3 PL ± .005 [.13] 2 PL ± .015 [.38] • REMOVE ALL BURRS AND SHARP EDGES R.01 MAX • CONCENTRICITY MACHINED EDA: .002 FIM • MACHINE TOOL MISMATCH .003 MAX	RH	7/5/2001
			CHK	DATE
			ENGR	DATE
			MJ	7/5/2001
			MFGR	DATE
			QA	DATE
NEXT ASSY	USED ON		RLSE	DATE
APPLICATION		THIRD ANGLE PROJECTION		

WERLATONE SINCE 1965 — 17 Jon Barrett Rd Patterson, NY 12563

TITLE: OUTLINE

SIZE	CAGE CODE	DWG NO	REV
B		10379-505	A

SCALE 1:1 — SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com