WERLATONE

Model C10536
Connectorized Directional Couplers



**PRODUCT DATA SHEET** **C10536**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Features:**

High Power  Wide Bandwidths  Small Size  Flat Coupling  Custom Designs Available

**Electrical Specifications:**

| | |
|---|---|
| Frequency: | 700 - 4200 MHz |
| Power: | 1000 W CW |
| Coupling: | 50 ± 1.0 dB Max. |
| Insertion Loss: | 0.2 dB Max. |
| Flatness: | ± 1.0 dB Max. |
| VSWR (ML): | 1.35:1 Max. |
| Directivity: | 15 dB Min. |

**Mechanical Specifications:**

| | |
|---|---|
| Type: | Connectorized |
| Material: | Aluminum 6061-T6 |
| Surface Finish: | Chem. Film Per MIL-DTL-5541F<br>Type II, Class 3 (Clear Iridite)<br>RoHS Compliant Available |
| Operating Temperature: | -55°C to +75°C |
| Storage Temperature: | -60°C to +85°C |
| Humidity: | 95% Non-Condensing |
| Size: | 2.15 x 2.0 x 1.36" |

**Connector Configurations:**

| Model | Input (J1) | Output (J2) | Fwd (J3) | Rev (J4) |
|---|---|---|---|---|
| C10536-20 | 7/16 Female | 7/16 Female | N Female | N Female |
| C10536-22 | 7/16 Female | 7/16 Female | SMA | SMA |
| C10536-78 | 7/8'' EIA Male | 7/16 Female | N Female | N Female |
| C10536-727 | 7/16 Male | 7/16 Female | N Female | N Female |
| C10536-728 | 7/16 Male | 7/16 Female | SMA | SMA |
| C10536-7724 | 7/16 Male | 7/16 Male | SMA | SMA |

**Werlatone**® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


Werlatone, Inc.All Rights Reserved






## Performance Data (Specifications subject to change without notice):


Coupling:





VSWR:




Insertion Loss:




Directivity:






Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

| REVISION HISTORY | | | |
|---|---|---|---|
| REV. | REVISION RECORD | DATE | APPROVED |
| - | INITIAL-RELEASE | 5/8/2015 | BW |
| A | ECN 9696 | 3/25/19 | RB |

**NOTES: UNLESS OTHERWISE SPECIFIED**
1. **MATERIAL: ALUMINUM 6061-T6**
2. **FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
3. **CONNECTORS:**
   **J1,J2: 7/16 FEMALE**
   **J3,J4: N FEMALE**




| | |
|---|---|
| NEXT ASSY | USED ON |
| APPLICATION | |

UNLESS OTHERWISE SPECIFIED
- INTERPRET DRAWING IAW MIL-STD-100
- DIMENSIONING PER ASME Y14.5M-2009
- PARENTHETICAL INFO FOR REF ONLY
- DIMENSIONS ARE IN INCHES
- DIMENSIONAL LIMITS APPLY BEFORE PROCESSES
- TOLERANCES:
  ANGLES ± 2°
  3 PL ± .005 [.13]
  2 PL ± .015 [.38]
- REMOVE ALL BURRS AND SHARP EDGES R.01 MAX
- CONCENTRICITY MACHINED DIA: .002 FIM
- MACHINE TOOL MISMATCH .003 MAX

THIRD ANGLE PROJECTION

| | | DATE |
|---|---|---|
| DWN | SD | 3/25/2019 |
| CHK | CS | 3/25/2019 |
| ENGR | | |
| MFGR | | |
| QA | | |
| RLSE | | |

WERLATONE| SINCE 1965
17 Jon Barrett Rd
Patterson, NY 12563

TITLE
OUTLINE

| SIZE | CAGE CODE | DWG NO | REV |
|---|---|---|---|
| B | | 21316-500 | A |

SCALE 1:1 SHEET1 OF1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com