



PRODUCT DATA SHEET

C8163W

3-Port Uni-Directional Coupler: Consists of a main line and a coupled line. One end of the coupled line is internally terminated, while the other end serves as a coupled port. Ideal for sampling and monitoring power in one direction at a given time. It is necessary to physically reverse the orientation of the unit to change from a forward to a reverse power measurement.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 100 - 1000 MHz
Power: 200 W CW
Coupling: 6 ± 1.0 dB Max.
Insertion Loss: 0.4 dB Max.
Flatness: ± 1.0 dB Max.
VSWR (ML): 1.30:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite), Black Epoxy Paint / White Epoxy Lettering
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 100% Condensing (O-Ring Sealed)
Size: 7.0 x 5.0 x 1.8"
Weight: 3 lbs.

Port Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)
C8163W-10	N Female	N Female	N Female

During normal operation, the uneven splitter will not require any heat dissipation. In the case of a failure in the cable connected to J2 or J3, however, the unit must be mounted to a heat spreader capable of dissipating 35 W CW.

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C8163W

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:





Insertion Loss:



Directivity:



DATE	SYM	REVISION RECORD	AUTH	DR	CK
2/24/04	REV.A	ECN:3434	RH		



THIS DRAWING CONTAINS INFORMATION
PROPRIETARY TO WERLATONE INC. AND
MAY NOT BE USED OR COPIED WITHOUT
THE WRITTEN CONSENT OF WERLATONE INC.

TOLERANCE				WERLATONE INC.	
XX +/- .015				SCALE	DRAWN BY: NH
XXX +/- .005					APPVD BY: CS
		TITLE :		OUTLINE	
		DATE	DRAWING NO:		
		07/09/03		10921-500A	

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com