PRODUCT DATA SHEET C3820

Non-Isolated Uneven Splitters (Taps): Utilized to un-evenly split a single run of 50 Ohm coaxial cable, hosting multiple frequency bands, so that a shorter corridor, tunnel, shaft, or hallway is provided a lesser portion of power on the main coaxial run than that required by a longer run. Non-Isolated Uneven Splitters are Bi-Directional, and unlike Directional Couplers, all ports can communicate with one another.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

 $\begin{array}{lll} \mbox{Frequency:} & 77 - 2200 \mbox{ MHz} \\ \mbox{Power:} & 100 \mbox{ W CW} \\ \mbox{Coupling:} & 6 \pm 1.0 \mbox{ dB Max.} \\ \mbox{Insertion Loss:} & 2.0 \mbox{ dB Max.} \\ \mbox{Flatness:} & \pm 1.0 \mbox{ dB Max.} \\ \mbox{VSWR (ML):} & 1.50:1 \mbox{ Max.} \end{array}$

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F

Type I Class 3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 20.0 x 4.75 x 1.78"

Weight: 6.25 lbs.

Port Configurations:

Input (J1) Output (J2) Fwd (J3) Model C3820-10 N Female N Female N Female C3820-20 7/16 Female 7/16 Female N Female C3820-24 7/16 Female 7/16 Female 7/16 Female

Werlatone® Broadband Non-Isolated Uneven Splitters (Taps) are designed to tolerate the most stringent operating conditions associated with Distributive Antenna Systems (DAS).


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


PRODUCT DATA SHEET C3820

Performance Data (Specifications subject to change without notice):

Coupling:




VSWR:



Frequency (MHz)


Insertion Loss:



For In-Building Applications



For In-Building Applications



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com