
PRODUCT DATA SHEET
C10224

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 800 - 2800 MHz
Power: 1000 W CW
Coupling: 60 ± 1.0 dB Max.
Insertion Loss: 0.2 dB Max.
Flatness: ± 0.75 dB Max.
VSWR (ML): 1.30:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 3.0 x 3.0 x 1.59"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10224-20	7/16 Female	7/16 Female	N Female	N Female
C10224-22	7/16 Female	7/16 Female	SMA	SMA
C10224-23	7/16 Female	7/16 Female	BNC	BNC
C10224-627	7/16 Female	7/16 Male	N Female	N Female
C10224-727	7/16 Male	7/16 Female	N Female	N Female
C10224-728	7/16 Male	7/16 Female	SMA	SMA

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C10224

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.



Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	5/13/2019	RB

- NOTES: UNLESS OTHERWISE SPECIFIED**
- MATERIAL: ALUMINUM 6061-T6**
 - FINISH: CHEM FILM PER MIL-DTL-5541F CLASS I TYPE 3 (YELLOW IRIDITE)**
 - CONNECTORS:**
J1, J2: 7/16 FEMALE
J3, J4: N FEMALE

UNLESS OTHERWISE SPECIFIED		OWN	DATE	 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563	
INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		SD	5/13/2019			
DIMENSIONS PER ASME Y14.5M-2009		CHK	DATE	OUTLINE		
DIMENSIONAL INFO FOR REF ONLY		CS	5/13/2019			
PARENTHESES ARE USED FOR REF ONLY		ENGR	DATE	SIZE CAGE CODE DWG NO B 10443-501		
DIMENSIONS ARE IN INCHES		INFR	DATE			
DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		QA	DATE	SCALE 1:1		
TOLERANCES:		RLSE	DATE			
ANGLES ± 2°		THIRD ANGLE PROJECTION 				SHEET 1 OF 1
3 PL ± .005 [13]						
2 PL ± .015 [38]		APPLICATION				
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX		NEXT ASSY USED ON				
CONCENTRICITY MACHINED DIA. .002 FIM						
MACHINE TOOL MISMATCH .003 MAX						

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com