


**PRODUCT DATA SHEET**
**C10364**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Features:**

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

**Electrical Specifications:**

Frequency:      700 - 6000 MHz  
 Power:          500 W CW  
 Coupling:        50 ± 1.0 dB Max.  
 Insertion Loss: 0.2 dB Max.  
 Flatness:        ± 1.0 dB Max.  
 VSWR (ML):    1.35:1 Max.  
 Directivity:     15 dB Min.

**Mechanical Specifications:**

Type:              Connectorized  
 Material:         Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F  
                       Type I Class 3 (Yellow Iridite)  
                       RoHS Compliant Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature: -60°C to +85°C  
 Humidity:        95% Non-Condensing  
 Size:              2.15 x 2.0 x 1.36"

**Connector Configurations:**


Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10364-20	7/16 Female	7/16 Female	N Female	N Female
C10364-22	7/16 Female	7/16 Female	SMA	SMA
C10364-727	7/16 Male	7/16 Female	N Female	N Female

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




## Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**  
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL-RELEASE	5/8/2015	BW
A	ECN 9696	3/25/19	RB

- NOTES: UNLESS OTHERWISE SPECIFIED**
- MATERIAL: ALUMINUM 6061-T6**
  - FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
  - CONNECTORS:**  
**J1,J2: 7/16 FEMALE**  
**J3,J4: N FEMALE**



UNLESS OTHERWISE SPECIFIED		DWN	DATE	WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563
INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		SD	3/25/2019		
DIMENSIONS FOR ASSEMBLY PER MIL-STD-1009		CHK	DATE	TITLE	
PARENTHEetical INFO FOR REF ONLY		CS	3/25/2019		
DIMENSIONS ARE IN INCHES		ENGR	DATE	<b>OUTLINE</b>	
DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		INFR	DATE		
TOLERANCES:		QA	DATE	SIZE	CAGE CODE
ANGLES ± 2°		RLSE	DATE	B	21316-500
3 PL ± .005 [1.3]				DWG NO	REV
2 PL ± .015 [3.8]					A
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX				SCALE	
CONCENTRICITY MACHINED DIA: .002 FIM				1:1	
MACHINE TOOL MISMATCH .003 MAX					SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com