



PRODUCT DATA SHEET C3587

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

 $\begin{array}{lll} \mbox{Frequency:} & 2 - 32 \mbox{ MHz} \\ \mbox{Power:} & 5,000 \mbox{ W CW} \\ \mbox{Coupling:} & 60 \pm 1.0 \mbox{ dB Max.} \\ \mbox{Insertion Loss:} & 0.05 \mbox{ dB Max.} \\ \mbox{Flatness:} & \pm 0.5 \mbox{ dB Max.} \\ \mbox{VSWR (ML):} & 1.05:1 \mbox{ Max.} \\ \mbox{Directivity:} & 20 \mbox{ dB Min.} \end{array}$

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F

Type I Class 3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 5.0 x 3.0 x 2.24"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C3587-10	N Female	N Female	N Female	N Female
C3587-12	N Female	N Female	SMA	SMA
C3587-13	N Female	N Female	BNC	BNC
C3587-20	7/16 Female 🥣	7/16 Female	N Female	N Female
C3587-30	LC Female	LC Female	N Female	N Female
C3587-33	LC Female	LC Female	BNC Female	BNC Female
C3587-61	HN Female	HN Female	N Female	N Female
C3587-63	HN Female	HN Female	SMA	SMA
C3587-64	HN Female	HN Female	SMA	SMA
C3587-503	SQS Female	SQS Female	BNC Female	BNC Female

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com






PRODUCT DATA SHEET C3587


Performance Data (Specifications subject to change without notice):








Directivity:





Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com