



PRODUCT DATA SHEET

C5597

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 0.1 - 1000 MHz
 Power: 300 W CW
 Coupling: 40 ± 1.0 dB Max.
 Insertion Loss: 0.5 dB Max.
 Flatness: ± 0.5 dB Max.
 VSWR (ML): 1.30:1 Max.
 Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
 Material: Aluminum 6061-T6
 Surface Finish: Chem. Film Per MIL-DTL-5541F
 Type I Class 3 (Yellow Iridite)
 RoHS Compliant Available
 Operating Temperature: -55°C to +75°C
 Storage Temperature: -60°C to +85°C
 Humidity: 95% Non-Condensing
 Size: 5.2 x 2.67 x 1.69"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C5597-10	N Female	N Female	N Female	N Female
C5597-12	N Female	N Female	SMA	SMA
C5597-13	N Female	N Female	BNC	BNC
C5597-714	N Male	N Female	N Female	N Female

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



WERLATONE

Model C5597




PRODUCT DATA SHEET


C5597

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION



This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/28/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
- CONNECTORS:**
J1-J4: SMA FEMALE



UNLESS OTHERWISE SPECIFIED										DWN	DATE		VERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563			
INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100										SD	2/11/2019						
DIMENSIONS PER ASME Y14.5M-2009										CHK	DATE						
PARENTHESES ARE IN INCHES										CS	2/11/2019						
DIMENSIONS ARE IN INCHES										ENGR	TITLE						
DIMENSIONAL LIMITS APPLY BEFORE PROCESSES										BKR	DATE	OUTLINE		SIZE	CAGE CODE	DWG NO	REV
TOLERANCES:										INFR	DATE						
ANGLES ± 2°										QA	DATE						
3 PL ± .005 [.13]										RLSE	DATE						
2 PL ± .015 [.38]																	
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX																	
CONCENTRICITY MACHINED DIA. .002 FIM																	
MACHINE TOOL MISMATCH .003 MAX																	
NEXT ASSY		USED ON		APPLICATION		THIRD ANGLE PROJECTION				SCALE		1:1.5		10407-501		SHEET 1 OF 1	

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com