

PRODUCT DATA SHEET

C6933

4-Port Bi-Directional Coupler: Similar to the 3-Port Uni-Directional Coupler, except that both ends of the coupled line serve as coupled ports. Convenient for simultaneously monitoring both forward and reverse power. The directivity of this coupler design is, however, dependent upon well matched 50 Ohm loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 60 - 600 MHz
 Power: 200 W CW
 Coupling: 6 ± 1.0 dB Max.
 Insertion Loss: 0.35 dB Max.
 Flatness: ± 1.0 dB Max.
 VSWR (ML): 1.20:1 Max.
 Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
 Material: Aluminum 6061-T6
 Surface Finish: Chem. Film Per MIL-DTL-5541F
 Type I Class 3 (Yellow Iridite)
 RoHS Compliant Available
 Operating Temperature: -55°C to +75°C
 Storage Temperature: -60°C to +85°C
 Humidity: 95% Non-Condensing
 Size: 6.0 x 4.0 x 0.75"
 Weight: 1 lb.

Port Configurations:


Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C6933-10	N Female	N Female	N Female	N Female
C6933-12	N Female	N Female	SMA	SMA
C6933-102	SMA	SMA	SMA	SMA

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



WERLATONE

Model C6933




PRODUCT DATA SHEET


C6933

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

This document contains proprietary information
which is the sole property of Werlatone, Inc.

REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	6/12/2019	RB



1. MATERIAL: ALUMINUM 6061-T6
2. FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)
3. CONNECTORS:
J1-J4: N FEMALE



UNLESS OTHERWISE SPECIFIED INTERPRET DRAWING IN ACCORDANCE WITH THE FOLLOWING DIMENSIONS ARE IN INCHES PARENT DIMENSIONS APPLY BEFORE PROCESSES TOLERANCES: ANGLES = 2° 3 P.L. ± .005 (13) 2 P.L. ± .015 (30) REMOVE ALL BURRS AND SHARP EDGES 8.01 MAX CONCENTRICITY MACHINED DIA. .002 FPM MACHINE TOOL RESTRICTION .001 MAX		OWN DATE SD 6/12/2019 CHK DATE CS 6/12/2019 ENGR DATE REFR DATE QA DATE RLSE DATE		 WERLATONE SINCE 1965 TITLE OUTLINE SIZE CAGE CODE DWG NO SCALE 1:25 10941-500		17 Jon Barrett Rd Patterson, NY 12565	
APPLICATION		THIRD ANGLE PROJECTION		REV A		SHEET 1 OF 1	

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com