
PRODUCT DATA SHEET
C6934

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 0.1 - 1000 MHz
Power: 150 W CW
Coupling: 30 ± 1.0 dB Max.
Insertion Loss: 1.2 dB Max.
Flatness: ± 0.5 dB Max.
VSWR (ML): 1.30:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 5.2 x 2.68 x 1.69"

Connector Configurations:


Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C6934-10	N Female	N Female	N Female	N Female
C6934-12	N Female	N Female	SMA	SMA
C6934-13	N Female	N Female	BNC	BNC
C6934-102	SMA	SMA	SMA	SMA

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



WERLATONE

Model C6934




PRODUCT DATA SHEET


C6934

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION

This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY

REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/28/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
- CONNECTORS:**
J1, J2: N FEMALE
J3, J4: SMA FEMALE

		UNLESS OTHERWISE SPECIFIED		OWN		DATE	 WERLATONE SINCE 1965		17 Jon Barrett Rd Patterson, NY 12563	
		INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		SD		2/11/2019	 WERLATONE SINCE 1965			
		DIMENSIONS PER ASME Y14.5M-2009		CHK		DATE				
		PARENTHESES FOR REF ONLY		CS		2/11/2019	TITLE			
		DIMENSIONS ARE IN INCHES		ENGR		DATE	OUTLINE			
		DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		BW		5/28/2008				
		TOLERANCES:		INFR		DATE	SCALE : 1.5		SHEET 1 OF 1	
		ANGLES ± 2°		QA		DATE				
		3 PL ± .005 [13]		RLSE		DATE	10407-502		A	
		2 PL ± .015 [38]								
		REMOVE ALL BURRS AND SHARP EDGES R.01 MAX								
		CONCENTRICITY MACHINED DIA. .002 FIM								
		MACHINE TOOL MISMATCH .003 MAX								
NEXT ASSY USED ON		APPLICATION		THIRD ANGLE PROJECTION						

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com