

PRODUCT DATA SHEET
C9271W

3-Port Uni-Directional Coupler: Consists of a main line and a coupled line. One end of the coupled line is internally terminated, while the other end serves as a coupled port. Ideal for sampling and monitoring power in one direction at a given time. It is necessary to physically reverse the orientation of the unit to change from a forward to a reverse power measurement.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 100 - 1000 MHz
Power: 100 W CW
Coupling: 10 ± 1.0 dB Max.
Insertion Loss: 0.5 dB Max.
Flatness: ± 1.0 dB Max.
VSWR (ML): 1.20:1 Max.
Directivity: 17 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: Watertight, 100% Condensing
Size: 7.05 x 3.03 x 1.2"
Weight: 2 lbs.

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)
C9271W-10	N Female	N Female	N Female
C9271W-12	N Female	N Female	SMA
C9271W-102	SMA	SMA	SMA

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C9271W

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:






Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISIONS			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN: 5677	6/7/2012	SC

		UNLESS OTHERWISE SPECIFIED		DWN	DATE	 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563			
		• INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-883C • CONFORM TO ASME Y14.5M-2009 • PARENT/CHILD INFO FOR REF ONLY • DIMENSIONS ARE IN INCHES • DIMENSIONAL LIMITS APPLY BEFORE PROCESSES • TOLERANCES: - ANGLES ± 2° 3 PL ± .005 2 PL ± .015 • REMOVE ALL BURRS AND SHARP EDGES R.01 MAX • CONCENTRICITY MACHINED DIA. .002 FDM • MACHINE TOOL PREPARATION .001 FDM		SC	6/7/2012					
				CHK	DATE	TITLE				
				ENGR	DATE					
				BW	6/7/2012					
				APPGR	DATE	C9271W-10B	SIZE	CAGE CODE	DWG NO	REV
				QA	DATE					
				RESE	DATE	B	28812	20865-500		A
						SCALE	1:2	SHEET 1 OF 1		
						DWG NO				
						REV				

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com