



PRODUCT DATA SHEET C9792

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

#### Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

## **Electrical Specifications:**

 $\begin{array}{lll} \mbox{Frequency:} & 30 - 520 \mbox{ MHz} \\ \mbox{Power:} & 10,000 \mbox{ W CW} \\ \mbox{Coupling:} & 70 \pm 1.0 \mbox{ dB Max.} \\ \mbox{Insertion Loss:} & 0.15 \mbox{ dB Max.} \\ \mbox{Flatness:} & \pm 0.75 \mbox{ dB Max.} \\ \mbox{VSWR (ML):} & 1.30:1 \mbox{ Max.} \\ \mbox{Directivity:} & 20 \mbox{ dB Min.} \end{array}$ 

# **Mechanical Specifications:**

Type: Connectorized Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F

Type I Class 3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 6" Line Section

### **Connector Configurations:**

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C9792-91	3 1/8" ÉIA	3 1/8" EIA	N Female	N Female
C9792-92	3 1/8" EIA	3 1/8" EIA	N Male	N Male
C9792-93	3 1/8" EIA	3 1/8" EIA	SMA	SMA
C9792-94	3 1/8" EIA	3 1/8" EIA	BNC	BNC

**Werlatone**® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.






PRODUCT DATA SHEET C9792


# Performance Data (Specifications subject to change without notice):





Frequency (MHz)

15 20 25 30 35 30 128 226 324 422 520 Frequency (MHz)



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com