



PRODUCT DATA SHEET

D10119

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency: 700 - 4200 MHz
 Power: 2000 W CW
 Insertion Loss: 0.3 dB Max.
 VSWR: 1.35:1 Max.
 Phase Balance: $\pm 6^\circ$ Max.
 Amplitude Balance: 0.3 dB Max.
 Isolation: Non-Isolated

Mechanical Specifications:

Type: Connectorized
 Material: Aluminum 6061-T6
 Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
 Operating Temperature: -55°C to +75°C
 Storage Temperature: -60°C to +85°C
 Weight: 5.0 lbs.
 Size:

Connector Configurations:


Model	Sum Port (J1)	Input/Output (J2-J5)
D10119-500	13-30 DIN (F)	N Female

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.



WERLATONE

Model D10119




PRODUCT DATA SHEET


D10119

Performance Data (Specifications subject to change without notice):

Insertion Loss:




VSWR:



Since 1965:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL-RELEASE	11/21/2014	BW



4X TAP 10-32 ∇ .45 [11.4]
SPACED 90° ON A 3.750 [95.3] \pm .003 BC



		UNLESS OTHERWISE SPECIFIED		DWN	DATE	 WERLATONE SINCE 1965 17 Jon Barrett Rd Patterson, NY 12563	A		
		INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100 DIMENSIONING PER ASME Y14.5M-2009 PARENTHESES ARE FOR REF ONLY DIMENSIONS ARE IN INCHES TOLERANCES: ANGLES ± 2 3 PL ± .005 2 PL ± .015 REMOVE ALL BURRS AND SHARP EDGES R.01 MAX CONCENTRICITY MACHINED DIA: .002 FIM MACHINED TOOL MISMATCH .002 MAX		CHK	DATE				
				ENGR	DATE				
				GP	DATE				
				MGR	DATE				
D10119				QA	DATE	D10119 4-WAY COMBINER/DIVIDER			
NEXT ASSY	USED ON			RLSE	DATE	SIZE	CAGE CODE	DWG NO	REV
APPLICATION		THIRD ANGLE PROJECTION				C	28812	21218-500	-
						SCALE	1:1		Sheet 1 of 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com