



PRODUCT DATA SHEET D5855

Werlatone® *Mismatch Tolerant*® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone**® designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

Electrical Specifications:

Frequency: 1 - 30 MHz
Power: 200 W CW
Insertion Loss: 0.2 dB Max.
VSWR: 1.20:1 Max.
Phase Balance: ± 3° Max.
Amplitude Balance: 0.1 dB Max.
Isolation: 25 dB Min.

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55° C to $+75^{\circ}$ C Storage Temperature: -60° C to $+85^{\circ}$ C

Weight: 3 lbs.

Size: 6.0 x 5.0 x 2.0"

Connector Configurations:

 Model
 Sum Port (J5)
 Input/Output (J1-J4)

 D5855-10
 N Female
 N Female

 D5855-12
 N Female
 SMA

 D5855-13
 N Female
 BNC

 D5855-102
 SMA
 SMA


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.






PRODUCT DATA SHEET D5855

Performance Data (Specifications subject to change without notice):





Frequency (MHz)

