



## PRODUCT DATA SHEET

D9002

**Werlatone® Mismatch Tolerant®** High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

### Features:

High Power      Wide Bandwidths      Small Size      High Isolation      Custom Designs Available

### Electrical Specifications:

Frequency: 80 - 1000 MHz  
 Power: 750 W CW  
 Insertion Loss: 0.6 dB Max.  
 VSWR: 1.35:1 Max.  
 Phase Balance:  $\pm 5^\circ$  Max.  
 Amplitude Balance: 0.3 dB Max.  
 Isolation: 17 dB Min.

### Mechanical Specifications:

Type: Connectorized  
 Material: Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature: -60°C to +85°C  
 Weight: 2.5 lbs.  
 Size: 5.0 x 4.7 x 1.4"

### Connector Configurations:

Model	Sum Port (J1)	Input/Output (J2-J5)
D9002-10	N Female	N Female
D9002-12	N Female	SMA

**When specified, Werlatone® High Power Combiners and RF Dividers** will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.




## PRODUCT DATA SHEET


D9002

### Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:



Isolation:



Phase Balance:





**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

[illegible]

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
6/6/13	B	8215	PR		

UNLESS OTHERWISE SPECIFIED		DWN	DATE	7/28/12	 WERLATONE SINCE 1965		17 Jon Barrett Rd Patterson, NY 12563	
* INTERPRET DRAWING INAW MIL-STD-100 * DIMENSIONING PER ASME Y14.5-2009 * PARENTHEetical INFO FOR REF ONLY * DIMENSIONS ARE IN INCHES * DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		CHK	DATE	7/28/12	TITLE		OUTLINE	
* TOLERANCES:		ENGR	DATE		USED ON			
ANGLES           ± 2° .XXX             ± .005 .XX              ± .015		MFR	DATE					
* HOLE TOLERANCES +.004/-.001 * REMOVE ALL BURRS AND SHARP EDGES .01 R MAX * CONCENTRICITY MACHINED DIA. .002 FIM * MACHINE TOOL MISMATCH .003 MAX		QA	DATE		SIZE	PAGE CODE	DWG NO	REV
					28812		20768-500	
THIRD ANGLE PROJECTION 		RLSE	DATE		SCALE	1:1		
						SHEET 1 OF 1		

**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com