

PRODUCT DATA SHEET D9585

**Werlatone**® *Mismatch Tolerant*® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone**® designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

#### Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

## **Electrical Specifications:**

Frequency: 30 - 520 MHz
Power: 2000 W CW
Insertion Loss: 0.6 dB Max.
VSWR: 1.35:1 Max.
Phase Balance: ± 5° Max.
Amplitude Balance: 0.3 dB Max.
Isolation: 15 dB min.

### **Mechanical Specifications:**

Type: Connectorized Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to +75°C Storage Temperature: -60°C to +85°C

Weight: 7 lbs.

Size: 7.75 x 7.0 x 2.6"

#### **Connector Configurations:**

Model	Input/Output (J1)	Input/Output (J2)	Sum Port (J3)
D9585-20	N Female	N Female	7/16 Female
D9585-41	N Female	N Female	SC Female
D9585-41STS	N Female STS	N Female STS	SC Female STS
D9585-47	N Female	SC Female	SC Female


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.




PRODUCT DATA SHEET D9585

# Performance Data (Specifications subject to change without notice):





30 128 226 324 422 520 Frequency (MHz)



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com