

PRODUCT DATA SHEET H1846

**Werlatone**® High Power 180° RF Hybrid Combiners/Dividers balance traditional technologies with disruptive microwave techniques. The outcome is a microwave component which provides an order of magnitude improvement over current capabilities. Our newest line of high power, patented 180° RF Hybrid Combiners/Dividers provides an incredible 5:1 bandwidth, while exhibiting exceptionally low loss and superior port-to-port isolation.

## **Features:**

High Power Wide Bandwidths Small Size Excellent Amplitude Balance

## **Electrical Specifications:**

Frequency: 88 - 108 MHz
Power: 1200 W CW
Insertion Loss 0.2 dB Max.
VSWR: 1.30:1 Max.
Phase Balance: 180° ± 3° Max.
Amplitude Balance: ± 0.1 dB Max.
Isolation: 20 dB Min.

## **Mechanical Specifications:**

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature:  $-55^{\circ}$ C to  $+75^{\circ}$ C Storage Temperature:  $-60^{\circ}$ C to  $+85^{\circ}$ C Size:  $3.0 \times 6.0 \times 2.25^{\circ}$ 

## **Connector Configurations:**

ModelSum Port (J1)Ext. Load Port (J2)Inputs (J3,J4)H1846-10N FemaleN Female

**Werlatone's** standard line of High Power 180° RF Hybrid Combiners/Dividers covers multiple octaves within a microwave device. Low frequency 180° Hybrid Combiner/Dividers employ proprietary ferrite transmission line techniques, similar to our 0° Combiners/Dividers. Insertion loss in both sum and difference ports is minimal, allowing the hybrid to handle high power over its frequency range. Custom requirements are welcome.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

