WERLATONE

Model QH8911

PRODUCT DATA SHEET **QH8911**

Our patented 3 dB 90° Hybrid Couplers provide:

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Connectorized Drop-In & Surface Mount

Electrical Specifications:

Frequency:	80 - 1000 MHz
Power:	250 W CW
Insertion Loss:	0.7 dB Max.
VSWR:	1.45:1 Max.
Phase Balance:	90° ± 5° Max.
Amplitude Balance:	± 1.0 dB Max.
Isolation:	18 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	0.75 lbs.
Size:	4.25 x 2.88 x 1.0''

Connector Configurations:

Model	**Sum Port (J1)**	**0°, -90° (J2,J3)**	**Ext. Load Port**
QH8911-10	N Female	N Female	Not Applicable
QH8911-12	N Female	SMA	Not Applicable
QH8911-102	SMA	SMA	Not Applicable


Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOUSRE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
4/7/2011	-	INITIAL RELEASE	NH	BW	BW



UNLESS OTHERWISE SPECIFIED					
· INTERPRET DRAWING IAW MIL-STD-100	DWN	NH	DATE	04/07/11	WERLATONE | SINCE 1965 — 17 Jon Barrett Rd, Patterson, NY 12563
· DIMENSIONING PER ASME Y14.5M-2009	CHK	BW	DATE	04/07/11	
· PARANTHETICAL INFO FOR REF ONLY	ENGR	BW	DATE	04/07/11	TITLE: OUTLINE
· DIMENSIONS ARE IN INCHES	QA		DATE		USED ON
· TOLERANCES: ANGLE ± 2°					
3 PL DECIMALS ± .005	RLSE		DATE		SIZE: A — CAGE CODE: 28812 — DWG NO: 20737-500 — REV: -
2 PL DECIMALS ± .015					SCALE: 1:2 — SHEET 1 OF 1
THIRD ANGLE PROJECTION					

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com