WERLATONE

Model WPM11326



**PRODUCT DATA SHEET** **WPM11326**

### Instantaneous & Simultaneous
- Local and/or Remote Monitoring
- Forward Power Reading/Monitoring (Watts or dBm)
- Reverse Power Reading/Monitoring (Watts or dBm)
- VSWR Readings (Watts, Return Loss, Rho)

### VSWR Alarm
- Customer can set up audio/visual alarm via relay contacts.
- Signal sent to closed loop.

### Temperature Monitoring (with alarm)
- One sensor, internal measurement, within Power Meter.
- One sensor, external measurement, to be placed by customer.

### General Purpose Inputs (6 ea) Multiple Use
- Track switch closures (assign to interlock group).
- Trigger alarm relay (sends email alert).
- RF presence status/alarm (saftey feature).
- Alarm, activated switch.

### Accessories:
- Single Channel and Multi-Channel Displays
- RF Digital Dashboard Spreadsheet Software, (Simultaneously Monitor Outputs of 30+ Power Meters
- PC Based Graphical User Interface Windows XP/7/8/10 Compatible

### Accuracy:
- ± 2% to Customer Calibration Standard, at preselected frequencies.
- ± 5% over a Multi-Octave Bandwidth
- Werlatone Calibration Traceable to (NIST) National Institute of Standards and Technology

### Power:
- AC Power Adapter (100/240 50-60 Hertz V AC)
- POE (Passive Over Ethernet, Optional POE Injector Kit Available
- Via RS485 (Via Single Channel or Multi-Channel Displays)

### Interface (Via):
- TCP/IP - SNMP and Browser Interface via Local Area Network
- RS232, Serial
- RS485 - Form Addressable Serial Network
- User ID and Password Protected for Access and Control
- Multiple units can be Networked and Simultaneously Monitored On-Site or Remotely (TCP/IP/SNMP/Serial)

RoHS Compliant Design Available
Custom Connector Configurations Available

### Electrical Specifications:

| | |
|---|---|
| Frequency: | 2 - 50 MHz |
| Power: | 10,000 W CW |

### Mechanical Specifications:

| | |
|---|---|
| Type: | Connectorized |
| Operating Temperature: | -55°C to +75°C |
| Storage Temperature: | -60°C to +85°C |

### Connector Configurations:

| Model | Input(J1) | Output(J2) |
|---|---|---|
| WPM11326-83 | 1 5/8" EIA | 1 5/8" EIA |


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved


RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.


| REVISION HISTORY | | | |
|---|---|---|---|
| REV. | REVISION RECORD | DATE | APPROVED |
| - | INITIAL RELEASE | 7/6/2020 | CS |
| A | ECN 9965 | 9/29/2020 | CS |



VIEW FOR REFERENCE ONLY




**NOTES: UNLESS OTHERWISE SPECIFIED**
**1. CONNECTORS: J1-J2 1 5/8 (EIA)**

| | |
|---|---|
| | |
| | |
| | |
| | |
| | |
| | WPM11073 |
| NEXT ASSY | USED ON |
| APPLICATION | |

UNLESS OTHERWISE SPECIFIED
- INTERPRET DRAWING IAW MIL-STD-100
- DIMENSIONING PER ASME Y14.5M-2009
- PARENTHETICAL INFO FOR REF ONLY
- DIMENSIONS ARE IN INCHES [mm]
- DIMENSIONAL LIMITS APPLY BEFORE PROCESSES
- TOLERANCES:
  ANGLES ± 2°
  3 PL ± .005 [.13]
  2 PL ± .015 [.4]
- REMOVE ALL BURRS AND SHARP EDGES R.01 MAX
- CONCENTRICITY MACHINED DIA: .002 FIM
- MACHINE TOOL MISMATCH .003 MAX

THIRD ANGLE PROJECTION

| | | |
|---|---|---|
| DWN | PLP | 7/24/2015 |
| CHK | CS | 7/6/2020 |
| ENGR | | |
| MFGR | | |
| QA | | |
| RLSE | | |

WERLATONE SINCE 1965
17 Jon Barrett Rd
Patterson, NY 12563

TITLE: OUTLINE

| SIZE | CAGE CODE | DWG NO | REV |
|---|---|---|---|
| B | 28812 | 21340-505 | A |

SCALE 1:2 SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com