WERLATONE

Model WPM11357

PRODUCT DATA SHEET **WPM11357**

Instantaneous & Simultaneous
- Local and/or Remote Monitoring
- Forward Power Reading/Monitoring (Watts or dBm)
- Reverse Power Reading/Monitoring (Watts or dBm)
- VSWR Readings (Watts, Return Loss, Rho)

VSWR Alarm
- Customer can set up audio/visual alarm via relay contacts.
- Signal sent to closed loop.

Temperature Monitoring (with alarm)
- One sensor, internal measurement, within Power Meter.
- One sensor, external measurement, to be placed by customer.

General Purpose Inputs (6 ea) Multiple Use
- Track switch closures (assign to interlock group).
- Trigger alarm relay (sends email alert).
- RF presence status/alarm (saftey feature).
- Alarm, activated switch.

Accessories:
- Single Channel and Multi-Channel Displays
- RF Digital Dashboard Spreadsheet Software, (Simultaneously Monitor Outputs of 30+ Power Meters
- PC Based Graphical User Interface Windows XP/7/8/10 Compatible

Accuracy:
- ± 2% to Customer Calibration Standard, at preselected frequencies.
- ± 5% over a Multi-Octave Bandwidth
- Werlatone Calibration Traceable to (NIST) National Institute of Standards and Technology

Power:
- AC Power Adapter (100/240 50-60 Hertz V AC)
- POE (Passive Over Ethernet, Optional POE Injector Kit Available
- Via RS485 (Via Single Channel or Multi-Channel Displays)

Interface (Via):
- TCP/IP - SNMP and Browser Interface via Local Area Network
- RS232, Serial
- RS485 - Form Addressable Serial Network
- User ID and Password Protected for Access and Control
- Multiple units can be Networked and Simultaneously Monitored On-Site or Remotely (TCP/IP/SNMP/Serial)

RoHS Compliant Design Available
Custom Connector Configurations Available

Electrical Specifications:

Frequency:	1.5 - 32 MHz
Power:	5,000 W CW

Mechanical Specifications:

Type:	Connectorized
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C

Connector Configurations:


Model	Input(J1)	Output(J2)
WPM11357-22	7/16 Female	7/16 Female
WPM11357-32	LC Female	LC Female
WPM11357-63	HN Male	HN Female

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	10/15/2018	CS



		UNLESS OTHERWISE SPECIFIED	DWN PLP	DATE 9/27/2018	WERLATONE SINCE 1965 — 17 Jon Barrett Rd, Patterson, NY 12563
		• INTERPRET DRAWING IAW MIL-STD-100 • DIMENSIONING PER ASME Y14.5M-2009 • PARENTHETICAL INFO FOR REF ONLY • DIMENSIONS ARE IN INCHES [mm] • DIMENSIONAL LIMITS APPLY BEFORE PROCESSES • TOLERANCES: ANGLES ± 2° 3 PL ± .005 [.13] 2 PL ± .015 [.4] • REMOVE ALL BURRS AND SHARP EDGES R.01 MAX • CONCENTRICITY MACHINED DIA: .002 FIM • MACHINE TOOL MISMATCH .003 MAX	CHK CS	DATE 10/15/2018	TITLE: OUTLINE
			ENGR	DATE	
			MFGR	DATE	
			QA	DATE	SIZE B | CAGE CODE 28812 | DWG NO 21650-500 | REV -
	WPM11380		RLSE	DATE	SCALE 1:2 | SHEET 1 OF 1
NEXT ASSY	USED ON				
APPLICATION		THIRD ANGLE PROJECTION			

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com