

PRODUCT DATA SHEET
QH11643
Our patented 3 dB 90° Hybrid Couplers provide:

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Connectorized Drop-In & Surface Mount

Electrical Specifications:

Frequency: 200 - 1000 MHz
Power: 200 W CW
Insertion Loss: 0.4 dB Max.
VSWR: 1.30:1 Max.
Phase Balance: 90° ± 5° dB Max.
Amplitude Balance: ± 0.7 dB Max.
Isolation: 18 dB Min.

Mechanical Specifications:

Type: Surface Mount
Plating Options: QH11643-Pb: Electrodeposited Tin/Lead
QH11643-Sn: Immersion Tin (RoHS Compliant)
QH11643-Ag: Immersion Silver (RoHS Compliant)
Size: 2.8 x 0.75 x 0.16"

Port Configurations:

J1	J2	J3	J4
Input	3 dB, 0°	3 dB, -90°	Isolated
3 dB, 0°	Input	Isolated	3 dB, -90°
3 dB, -90°	Isolated	Input	3 dB, 0°
Isolated	3 dB, 90°	3 dB, 0°	Input

Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.




PRODUCT DATA SHEET


QH11643

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION

This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY



REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	3/9/2018	BW
A	ECN 9543	3/30/2018	BW

NOTES: UNLESS OTHERWISE SPECIFIED

- SEE SMT APPLICATION NOTE FOR FURTHER INFORMATION

P/N	FINISH TYPE
QH11643-Ag	RoHS Imm. Silver
QH11643-Au	RoHS Nickel Gold
QH11643-Pb	ED Tin/Lead
QH11643-Sn	RoHS Imm. Tin

PORT CONFIGURATIONS			
J1	J2	J3	J4
Input	3 dB, 0°	3 dB, -90°	Isolated
3 dB, 0°	Input	Isolated	3 dB, -90°
3 dB, -90°	Isolated	Input	3 dB, 0°
Isolated	3 dB, -90°	3 dB, 0°	Input

		UNLESS OTHERWISE SPECIFIED		DWN	DATE	 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563	
INTERPRET DRAWING IAW MIL-STD-100			GP	GP	3/9/2018		TITLE OUTLINE, QH11643 90° HYBRID COUPLER, 200-1000 MHz, 200 W	REV A
DIMENSIONING PER ASME Y14.5M-2009			CHK	CHK	DATE			
PARENTHEetical INFO FOR REF ONLY			PR	PR	3/9/2018			
DIMENSIONS ARE IN INCHES			ENGR	ENGR	DATE			
DIMENSIONAL LIMITS APPLY BEFORE PROCESSING			GP	GP	3/9/2018	SIZE A	CAGE CODE 28812	DWG NO 21596-500
TOLERANCES:			MFGR	MFGR	DATE			
ANGLES ± 2°			QA	QA	DATE			
3 PL ± .005			RLSE	RLSE	DATE			
2 PL ± .015			THIRD ANGLE PROJECTION 		SCALE 1:1		SHEET 1 OF 1	
REMOVE BURRS AND SHARP EDGES R.01 MAX								
CONCENTRICITY MACHINED DIA: .002 FIM								
MACHINE TOOL MISMATCH .003 MAX								
NEXT ASSY QH11643		USED ON APPLICATION						

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com